

PGP-ADJ

As Hunter's original rotor, the PGP-ADJ delivers unsurpassed reliability, durability, versatility, and value, keeping it the professional's choice year after year.

KEY BENEFITS

- Three types of nozzles available for various landscapes: red standard, blue standard, grey low-angle
- Adjustable arc from 40° to 360° to keep water in the appropriate areas
- Factory-installed rubber cover for safety
- Through-the-top arc adjustment for easy installation
- QuickCheck™ Arc Mechanism for fast arc adjustment

OPERATING SPECIFICATIONS

- Nozzle choices: 27
- Radius: 6.4 to 15.8 m
- Flow: 0.10 to 3.22 m³/hr; 1.7 to 53.7 l/min
- Recommended pressure range: 1.7 to 4.5 bar; 170 to 450 kPa
- Operating pressure range: 1.4 to 7.0 bar; 140 to 700 kPa
- Precipitation rate: 10 mm/hr approximately
- Nozzle trajectory: standard = 25°, low-angle = 13°
- Warranty period: 2 years

FACTORY-INSTALLED OPTIONS

- Red 5 to 8 Nozzles, Blue 1.5 to 4.0 Nozzles

USER-INSTALLED OPTIONS

- Drain Check Valve (up to 1 m of elevation) P/N 142300SP



PGP-ADJ

Easy arc and radius adjustment

Radius: **6.4 to 15.8 m**
Flow: **0.10 to 3.22 m³/hr; 1.7 to 53.7 l/min**



PGP-ADJ

Overall height: 19 cm
Pop-up height: 10 cm
Exposed diameter: 4 cm
Inlet size: ¾"

ROTORS

PGP-ADJ - SPECIFICATION BUILDER: ORDER 1 + 2 + 3		
1 Model	2 Standard Features	3 Feature Options
PGP-ADJ-B = 10 cm pop-up	Adjustable arc with blue nozzle rack	1.5 to 4.0 = Factory-installed blue nozzle number
PGP-ADJ = 10 cm pop-up	Adjustable arc with red nozzle rack	5 to 8 = Factory-installed red nozzle number

Examples:

PGP-ADJ = 10 cm pop-up, adjustable arc
PGP-ADJ-B-3.0 = 10 cm pop-up, adjustable arc, and Blue 3.0 Nozzle
PGP-ADJ -07 = 10 cm pop-up, adjustable arc, and Red 7 Nozzle

PGP-ADJ Red Nozzle



PGP-ADJ-B BLUE NOZZLE PERFORMANCE DATA

Nozzle	Pressure		Radius	Flow		Precip mm/hr	
	bar	kPa	m	m³/hr	l/min	■	▲
1.5 ● Blue	1.7	170	8.8	0.27	4.5	7	8
	2.0	200	9.1	0.29	4.8	7	8
	2.5	250	9.4	0.32	5.4	7	8
	3.0	300	9.8	0.35	5.9	7	9
	3.5	350	9.8	0.38	6.4	8	9
	4.0	400	9.8	0.41	6.8	9	10
	4.5	450	9.4	0.43	7.2	10	11
2.0 ● Blue	1.7	170	10.1	0.32	5.4	6	7
	2.0	200	10.1	0.35	5.8	7	8
	2.5	250	10.1	0.39	6.5	8	9
	3.0	300	10.4	0.43	7.2	8	9
	3.5	350	10.4	0.47	7.8	9	10
	4.0	400	10.4	0.50	8.3	9	11
	4.5	450	10.4	0.53	8.8	10	11
2.5 ● Blue	1.7	170	10.1	0.39	6.6	8	9
	2.0	200	10.4	0.43	7.1	8	9
	2.5	250	10.7	0.48	8.0	8	10
	3.0	300	10.7	0.54	8.9	9	11
	3.5	350	10.7	0.58	9.7	10	12
	4.0	400	10.7	0.62	10.4	11	13
	4.5	450	10.7	0.66	11.1	12	13
3.0 ● Blue	1.7	170	10.7	0.50	8.4	9	10
	2.0	200	10.7	0.54	9.1	10	11
	2.5	250	11.0	0.61	10.2	10	12
	3.0	300	11.6	0.68	11.4	10	12
	3.5	350	11.9	0.74	12.3	10	12
	4.0	400	11.9	0.79	13.2	11	13
	4.5	450	11.9	0.84	14.0	12	14
4.0 ● Blue	1.7	170	11.3	0.68	11.3	11	12
	2.0	200	11.6	0.73	12.2	11	13
	2.5	250	11.9	0.81	13.6	12	13
	3.0	300	12.2	0.90	15.0	12	14
	3.5	350	12.2	0.97	16.2	13	15
	4.0	400	12.5	1.04	17.3	13	15
	4.5	450	12.5	1.10	18.3	14	16
5.0 ● Blue	1.7	170	11.3	0.84	14.0	13	15
	2.0	200	11.6	0.91	15.2	14	16
	2.5	250	11.9	1.02	17.1	15	17
	3.0	300	12.8	1.14	19.0	14	16
	3.5	350	12.8	1.24	20.6	15	17
	4.0	400	12.8	1.32	22.1	16	19
	4.5	450	12.8	1.41	23.4	17	20
6.0 ● Blue	1.7	170	11.6	1.01	16.8	15	17
	2.0	200	11.9	1.09	18.2	15	18
	2.5	250	12.2	1.22	20.4	16	19
	3.0	300	13.1	1.36	22.7	16	18
	3.5	350	13.1	1.47	24.5	17	20
	4.0	400	13.4	1.57	26.2	18	20
	4.5	450	13.4	1.67	27.9	19	21
8.0 ● Blue	1.7	170	11.3	1.35	22.5	21	25
	2.0	200	11.9	1.46	24.3	21	24
	2.5	250	12.5	1.63	27.2	21	24
	3.0	300	13.4	1.81	30.2	20	23
	3.5	350	13.7	1.95	32.6	21	24
	4.0	400	14.0	2.09	34.8	21	25
	4.5	450	14.0	2.22	36.9	23	26

Note:

All precipitation rates are calculated for 180° operation. For the precipitation rate of a 360° sprinkler, divide by 2.


PGP-ADJ GREY LOW-ANGLE NOZZLE PERFORMANCE DATA

Nozzle	Pressure		Radius	Flow		Precip mm/hr	
	bar	kPa	m	m³/hr	l/min	■	▲
4 ● LA Grey	1.7	170	6.4	0.30	4.9	14	17
	2.0	200	6.7	0.32	5.3	14	16
	2.5	250	7.0	0.35	5.9	14	17
	3.0	300	7.3	0.39	6.5	15	17
	3.5	350	7.9	0.42	7.0	13	15
	4.0	400	8.5	0.45	7.5	12	14
	4.5	450	8.5	0.47	7.9	13	15
5 ● LA Grey	1.7	170	7.3	0.33	5.6	12	14
	2.0	200	7.6	0.36	6.0	12	14
	2.5	250	7.9	0.40	6.7	13	15
	3.0	300	8.2	0.45	7.4	13	15
	3.5	350	8.5	0.48	8.0	13	15
	4.0	400	8.8	0.52	8.6	13	15
	4.5	450	9.1	0.55	9.1	13	15
6 ● LA Grey	1.7	170	8.8	0.44	7.3	11	13
	2.0	200	9.1	0.47	7.9	11	13
	2.5	250	9.4	0.53	8.8	12	14
	3.0	300	9.8	0.59	9.8	12	14
	3.5	350	10.1	0.64	10.6	13	15
	4.0	400	10.7	0.68	11.3	12	14
	4.5	450	10.7	0.72	12.0	13	15
7 ● LA Grey	1.7	170	8.5	0.58	9.7	16	18
	2.0	200	8.8	0.62	10.3	16	18
	2.5	250	9.4	0.68	11.4	15	18
	3.0	300	10.1	0.75	12.5	15	17
	3.5	350	10.7	0.80	13.3	14	16
	4.0	400	11.3	0.85	14.1	13	15
	4.5	450	11.3	0.89	14.8	14	16
8 ● LA Grey	1.7	170	9.1	0.71	11.8	17	20
	2.0	200	9.4	0.76	12.7	17	20
	2.5	250	9.8	0.84	14.1	18	20
	3.0	300	10.4	0.93	15.5	17	20
	3.5	350	11.3	1.00	16.6	16	18
	4.0	400	11.6	1.06	17.6	16	18
	4.5	450	11.6	1.12	18.6	17	19
9 ● LA Grey	1.7	170	9.8	0.89	14.9	19	22
	2.0	200	10.1	0.96	16.0	19	22
	2.5	250	10.7	1.07	17.9	19	22
	3.0	300	11.3	1.19	19.8	19	22
	3.5	350	12.2	1.28	21.3	17	20
	4.0	400	12.8	1.37	22.8	17	19
	4.5	450	12.8	1.45	24.1	18	20
10 ● LA Grey	1.7	170	10.1	1.17	19.5	23	27
	2.0	200	10.7	1.26	21.0	22	26
	2.5	250	11.3	1.40	23.4	22	25
	3.0	300	11.6	1.55	25.9	23	27
	3.5	350	12.2	1.67	27.8	22	26
	4.0	400	12.8	1.78	29.7	22	25
	4.5	450	12.8	1.89	31.4	23	27

Note:

All precipitation rates are calculated for 180° operation. For the precipitation rate of a 360° sprinkler, divide by 2.

PGP-ADJ NOZZLES



Blue
(P/N 665300)



Grey
(P/N 233200)



PGP-ADJ RED NOZZLE PERFORMANCE DATA

Nozzle	Pressure bar kPa	Radius m	Flow m³/hr l/min	Precip mm/hr ■ ▲
1 ● Red	1.7 170	8.2	0.10 1.7	3 3
	2.0 200	8.5	0.11 1.8	3 3
	2.5 250	8.5	0.13 2.1	4 4
	3.0 300	8.8	0.15 2.4	4 4
	3.5 350	8.8	0.16 2.7	4 5
	4.0 400	9.1	0.18 2.9	4 5
2 ● Red	4.5 450	9.1	0.19 3.2	5 5
	1.7 170	8.5	0.14 2.4	4 5
	2.0 200	8.8	0.16 2.6	4 5
	2.5 250	8.8	0.17 2.9	4 5
	3.0 300	9.1	0.19 3.2	5 5
	3.5 350	9.1	0.21 3.5	5 6
3 ● Red	4.0 400	9.4	0.22 3.7	5 6
	4.5 450	9.4	0.23 3.9	5 6
	1.7 170	8.8	0.18 3.0	5 5
	2.0 200	9.1	0.20 3.3	5 5
	2.5 250	9.1	0.22 3.7	5 6
	3.0 300	9.4	0.25 4.1	6 6
4 ● Red	3.5 350	9.4	0.27 4.5	6 7
	4.0 400	9.8	0.29 4.8	6 7
	4.5 450	9.8	0.31 5.1	6 7
	1.7 170	9.4	0.24 4.1	5 6
	2.0 200	9.8	0.27 4.4	6 6
	2.5 250	9.8	0.30 5.0	6 7
5 ● Red	3.0 300	10.1	0.34 5.6	7 8
	3.5 350	10.1	0.37 6.2	7 8
	4.0 400	10.4	0.40 6.6	7 9
	4.5 450	10.4	0.43 7.1	8 9
	1.7 170	10.1	0.33 5.5	7 8
	2.0 200	10.4	0.36 5.9	7 8
6 ● Red	2.5 250	10.4	0.39 6.5	7 8
	3.0 300	11.0	0.43 7.2	7 8
	3.5 350	11.6	0.46 7.7	7 8
	4.0 400	11.6	0.49 8.1	7 8
	4.5 450	11.6	0.51 8.6	8 9
	1.7 170	10.1	0.42 6.9	8 10
7 ● Red	2.0 200	10.4	0.45 7.5	8 10
	2.5 250	10.7	0.51 8.5	9 10
	3.0 300	11.0	0.57 9.4	9 11
	3.5 350	11.6	0.61 10.2	9 11
	4.0 400	11.6	0.66 10.9	10 11
	4.5 450	11.9	0.70 11.6	10 11
8 ● Red	1.7 170	10.1	0.54 9.0	11 12
	2.0 200	10.4	0.58 9.7	11 12
	2.5 250	11.0	0.65 10.8	11 12
	3.0 300	11.6	0.72 12.0	11 12
	3.5 350	12.2	0.78 12.9	10 12
	4.0 400	12.2	0.83 13.8	11 13
9 ● Red	4.5 450	12.2	0.88 14.6	12 14
	1.7 170	11.0	0.66 11.0	11 13
	2.0 200	11.3	0.71 11.8	11 13
	2.5 250	11.6	0.79 13.2	12 14
	3.0 300	11.9	0.87 14.5	12 14
	3.5 350	12.5	0.94 15.6	12 14
10 ● Red	4.0 400	12.5	1.00 16.6	13 15
	4.5 450	12.8	1.05 17.6	13 15
	1.7 170	11.3	0.73 12.2	11 13
	2.0 200	11.6	0.80 13.4	12 14
	2.5 250	11.6	0.92 15.4	14 16
	3.0 300	12.5	1.05 17.5	13 16
11 ● Red	3.5 350	13.4	1.15 19.2	13 15
	4.0 400	13.4	1.25 20.9	14 16
	4.5 450	13.7	1.35 22.4	14 17
	2.0 200	12.2	1.14 19.0	15 18
	2.5 250	12.8	1.29 21.4	16 18
	3.0 300	13.4	1.44 24.0	16 18
12 ● Red	3.5 350	14.0	1.56 26.1	16 18
	4.0 400	14.3	1.68 28.0	16 19
	4.5 450	14.3	1.79 29.9	17 20
	5.0 500	14.6	1.90 31.7	18 21
	2.0 200	12.8	1.55 25.9	19 22
	2.5 250	13.7	1.73 28.7	18 21
13 ● Red	3.0 300	14.0	1.90 31.7	19 22
	3.5 350	14.6	2.05 34.1	19 22
	4.0 400	14.9	2.18 36.3	20 23
	4.5 450	15.2	2.30 38.4	20 23
	5.0 500	15.5	2.42 40.4	20 23
	2.0 200	12.8	2.03 33.8	25 29
14 ● Red	2.5 250	13.4	2.26 37.7	25 29
	3.0 300	14.3	2.51 41.8	24 28
	3.5 350	14.6	2.70 45.0	25 29
	4.0 400	14.9	2.88 48.1	26 30
	4.5 450	15.2	3.06 50.9	26 30
	5.0 500	15.8	3.22 53.7	26 30

PGP-ADJ RED NOZZLE PERFORMANCE DATA

Nozzle	Pressure bar kPa	Radius m	Flow m³/hr l/min	Precip mm/hr ■ ▲
8 ● Red	1.7 170	11.0	0.66 11.0	11 13
	2.0 200	11.3	0.71 11.8	11 13
	2.5 250	11.6	0.79 13.2	12 14
	3.0 300	11.9	0.87 14.5	12 14
	3.5 350	12.5	0.94 15.6	12 14
	4.0 400	12.5	1.00 16.6	13 15
9 ● Red	4.5 450	12.8	1.05 17.6	13 15
	1.7 170	11.3	0.73 12.2	11 13
	2.0 200	11.6	0.80 13.4	12 14
	2.5 250	11.6	0.92 15.4	14 16
	3.0 300	12.5	1.05 17.5	13 16
	3.5 350	13.4	1.15 19.2	13 15
10 ● Red	4.0 400	13.4	1.25 20.9	14 16
	4.5 450	13.7	1.35 22.4	14 17
	2.0 200	12.2	1.14 19.0	15 18
	2.5 250	12.8	1.29 21.4	16 18
	3.0 300	13.4	1.44 24.0	16 18
	3.5 350	14.0	1.56 26.1	16 18
11 ● Red	4.0 400	14.3	1.68 28.0	16 19
	4.5 450	14.3	1.79 29.9	17 20
	5.0 500	14.6	1.90 31.7	18 21
	2.0 200	12.8	1.55 25.9	19 22
	2.5 250	13.7	1.73 28.7	18 21
	3.0 300	14.0	1.90 31.7	19 22
12 ● Red	3.5 350	14.6	2.05 34.1	19 22
	4.0 400	14.9	2.18 36.3	20 23
	4.5 450	15.2	2.30 38.4	20 23
	5.0 500	15.5	2.42 40.4	20 23
	2.0 200	12.8	2.03 33.8	25 29
	2.5 250	13.4	2.26 37.7	25 29
13 ● Red	3.0 300	14.3	2.51 41.8	24 28
	3.5 350	14.6	2.70 45.0	25 29
	4.0 400	14.9	2.88 48.1	26 30
	4.5 450	15.2	3.06 50.9	26 30
	5.0 500	15.8	3.22 53.7	26 30

Note:

All precipitation rates are calculated for 180° operation. For the precipitation rate of a 360° sprinkler, divide by 2.

PGP-ADJ NOZZLES



Red
(P/N 130900)

