

PRS30

To maintain consistent performance and reduce water waste, the PRS30 is pressure-regulated to an optimal pressure of 2.1 bar; 210 kPa.

KEY BENEFITS

- Industry's strongest spray body for years of reliable performance
- Pressure-regulated to 2.1 bar; 210 kPa for optimal nozzle performance
- Brown cap for easy field identification
- Co-moulded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks, even with a loose cap
- FloGuard technology option eliminates water waste in the event of a missing nozzle

ADDITIONAL FEATURES

- Directional flush plug design for cleaner installation
- Interchangeable components for easier servicing, retrofits, and upgrades
- Heavy-duty spring for consistent riser retraction
- Check valve option eliminates low-head drainage

OPERATING SPECIFICATIONS

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa
- Warranty period: 5 years

FACTORY-INSTALLED OPTIONS

- Check valve available for 10 cm, 15 cm, and 30 cm models (up to 4.3 m of elevation)
- Reclaimed water identification
- FloGuard technology available for check valve models

USER-INSTALLED OPTIONS

- Check valve (up to 4.3 m of elevation; P/N 437400SP)
- Reclaimed water ID cap (P/N 458560SP)
- Snap-on reclaimed cover (P/N PROS-RC-CAP-SP)
- Shutoff cap (P/N 213600SP)
- Shutoff nozzle (P/N 916400SP)



PRS30 Reclaimed

PRS30 models include optional factory-installed purple reclaimed caps.



PROS-00-PRS30
Retracted height: 11 cm
Inlet size: ½"



PROS-04-PRS30
Retracted height: 15.5 cm
Pop-up height: 10 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



FloGuard Technology



[A] **PROS-06-SI-PRS30**
[B] **PROS-06-PRS30**
Retracted height: 22.5 cm
Pop-up height: 15 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



[A] **PROS-12-SI-PRS30**
[B] **PROS-12-PRS30**
Retracted height: 41 cm
Pop-up height: 30 cm
Exposed diameter: 5.7 cm
Inlet size: ½"

PRS30 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Feature Options	3 Specialty Options
PROS-00-PRS30 = 2.1 bar regulated shrub adapter	(blank) = No option	(blank) = No option
PROS-04-PRS30 = 2.1 bar regulated 10 cm pop-up	CV = Factory-installed drain check valve (pop-up models only)	R = Factory-installed reclaimed body cap
PROS-06-PRS30 = 2.1 bar regulated 15 cm pop-up		F = FloGuard technology
PROS-12-PRS30 = 2.1 bar regulated 30 cm pop-up		F-R = FloGuard technology with reclaimed body cap

PRS30 (SIDE INLET) MODELS

Model

PROS-06-SI-PRS30 = 2.1 bar regulated 15 cm pop-up with side inlet

PROS-12-SI-PRS30 = 2.1 bar regulated 30 cm pop-up with side inlet

Examples:

- PROS-06-SI-PRS30** = 15 cm pop-up with side inlet regulated at 2.1 bar; 210 kPa
- PROS-06-PRS30-CV** = 15 cm pop-up regulated at 2.1 bar; 210 kPa, drain check valve
- PROS-12-PRS30-CV-F-R** = 30 cm pop-up regulated at 2.1 bar; 210 kPa, drain check valve, and FloGuard technology with reclaimed body cap

Compatible with:



Pro Adjustable Nozzles
Page 70
Pro-Spray Fixed Arc Nozzles
Page 74