

PRO FIXED NOZZLES

Pro Fixed Nozzles are designed for high accuracy within a variety of landscape shapes and sizes.

KEY BENEFITS

- Clean edges for a defined pattern with better wind resistance
- Large water droplets minimise misting with better uniformity
- Sturdy construction ensures reliable performance
- Colour-coded for easy field identification

OPERATING SPECIFICATIONS

- Recommended operating pressure: 2.1 bar; 210 kPa
- Pair with Pro-Spray™ PRS30 Sprinkler Bodies for pressure regulation to 2.1 bar; 210 kPa
- Warranty period: 2 years

PRO FIXED NOZZLES						
ARC	5	8	10	12	15	17
Q						
T	Use 4A/6A Nozzle					Use 17A Nozzle
H						
F						Use 17A Nozzle
	1.5 m	2.4 m	3.0 m	3.7 m	4.6 m	5.2 m

PRO FIXED NOZZLES PERFORMANCE DATA

**5**
 1.5 m radius
 Fixed: ¼, ½, Full
 Trajectory: 0°

● Blue

8
 2.4 m radius
 Fixed: ¼, ½, Full
 Trajectory: 15°

● Brown

10
 3.0 m radius
 Fixed: ¼, ½, Full
 Trajectory: 15°

● Red

Arc	Position	Pressure		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr	
		bar	kPa		m³/hr	l/min	■	▲		m³/hr	l/min	■	▲		m³/hr	l/min	■	▲
90° 	Q	1.0	100	1.1	0.02	0.30	60	69	1.8	0.04	0.62	46	53	2.4	0.07	1.08	45	52
		1.5	150	1.3	0.02	0.38	54	62	2.1	0.05	0.84	46	53	2.7	0.08	1.33	44	51
		2.1	210	1.5	0.03	0.46	49	57	2.4	0.05	0.91	38	44	3.0	0.09	1.57	42	48
		2.5	250	1.7	0.03	0.51	42	49	2.7	0.06	0.98	32	37	3.3	0.10	1.71	38	44
		3.0	300	1.8	0.03	0.53	39	45	2.7	0.06	1.10	36	42	3.4	0.11	1.85	38	44
120° 	T	1.0	100	Use 4A or 6A Nozzle					1.8	0.05	0.83	46	53	2.4	0.09	1.44	45	52
		1.5	150						2.1	0.07	1.10	45	52	2.7	0.11	1.77	44	50
		2.1	210						2.4	0.07	1.21	38	44	3.0	0.13	2.09	42	48
		2.5	250						2.7	0.08	1.32	33	38	3.3	0.14	2.31	38	44
		3.0	300						2.7	0.09	1.44	36	41	3.4	0.15	2.50	39	45
180° 	H	1.0	100	1.1	0.04	0.60	60	69	1.8	0.08	1.33	49	57	2.4	0.13	2.17	45	52
		1.5	150	1.3	0.05	0.76	54	62	2.1	0.10	1.63	44	51	2.7	0.16	2.65	44	50
		2.1	210	1.5	0.06	0.87	49	57	2.4	0.11	1.80	38	43	3.0	0.19	3.14	42	48
		2.5	250	1.7	0.06	0.95	42	49	2.7	0.12	1.93	32	37	3.3	0.22	3.60	40	46
		3.0	300	1.8	0.06	1.04	39	44	2.7	0.13	2.10	35	40	3.4	0.23	3.90	40	47
360° 	F	1.0	100	1.1	0.07	1.20	60	69	1.8	0.16	2.67	49	57	2.4	0.26	4.33	45	52
		1.5	150	1.3	0.09	1.52	54	62	2.1	0.20	3.33	45	52	2.7	0.32	5.31	44	50
		2.1	210	1.5	0.11	1.85	49	57	2.4	0.22	3.67	38	44	3.0	0.38	6.28	42	48
		2.5	250	1.7	0.12	2.04	42	49	2.7	0.24	4.01	33	38	3.3	0.41	6.85	38	44
		3.0	300	1.8	0.12	2.10	39	45	2.7	0.26	4.35	36	41	3.4	0.42	6.97	36	42

Bold = Recommended pressure

Pro Fixed Nozzles



PRO FIXED NOZZLES PERFORMANCE DATA



12 3.7 m radius
Fixed: ¼, ⅓, ½, ⅔, ¾, Full
● Green Trajectory: 28°

15 4.6 m radius
Fixed: ¼, ⅓, ½, ⅔, ¾, Full
● Black Trajectory: 28°

17 5.2 m radius
Fixed: ¼, ½
● Grey Trajectory: 28°

Arc	Position	Pressure		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr	
		bar	kPa		m³/hr	l/min	■	▲		m³/hr	l/min	■	▲		m³/hr	l/min	■	▲
90° 	Q	1.0	100	3.0	0.10	1.58	42	49	3.9	0.15	2.50	39	46	4.7	0.19	3.17	34	40
		1.5	150	3.4	0.12	2.00	42	48	4.2	0.18	3.06	42	48	4.9	0.23	3.88	39	45
		2.1	210	3.7	0.15	2.43	43	49	4.6	0.22	3.62	41	47	5.2	0.28	4.59	41	47
		2.5	250	4.0	0.16	2.69	40	47	4.9	0.24	3.95	39	46	5.5	0.30	5.01	40	46
		3.0	300	4.0	0.18	2.95	44	51	5.2	0.26	4.32	38	44	5.8	0.32	5.30	38	44
120° 	T	1.0	100	3.0	0.13	2.11	42	49	3.9	0.20	3.33	39	46	Use 17A Nozzle				
		1.5	150	3.4	0.16	2.67	42	48	4.2	0.24	4.08	42	48					
		2.1	210	3.7	0.19	3.25	43	49	4.6	0.29	4.83	41	47					
		2.5	250	4.0	0.22	3.67	41	48	4.9	0.32	5.27	40	46					
		3.0	300	4.0	0.24	3.94	44	51	5.2	0.35	5.75	38	44					
180° 	H	1.0	100	3.0	0.19	3.17	42	49	3.9	0.30	5.00	39	46	4.7	0.38	6.33	34	40
		1.5	150	3.4	0.24	4.01	42	48	4.2	0.37	6.12	42	48	4.9	0.47	7.76	39	45
		2.1	210	3.7	0.29	4.87	43	49	4.6	0.43	7.25	41	47	5.2	0.55	9.18	41	47
		2.5	250	4.0	0.32	5.39	40	47	4.9	0.47	7.91	40	46	5.5	0.60	10.01	40	46
		3.0	300	4.0	0.35	5.75	43	50	5.2	0.49	8.18	36	42	5.8	0.64	10.06	38	44
360° 	F	1.0	100	3.0	0.38	6.33	42	49	3.9	0.60	10.00	39	46	Use 17A Nozzle				
		1.5	150	3.4	0.48	8.01	42	48	4.2	0.73	12.25	42	48					
		2.1	210	3.7	0.58	9.74	43	49	4.6	0.87	14.49	41	47					
		2.5	250	4.0	0.65	10.78	40	47	4.9	0.95	15.81	40	46					
		3.0	300	4.0	0.70	11.73	44	51	5.2	0.99	16.50	37	42					

Bold = Recommended pressure