

# ECO-WRAP™

Subsurface Irrigation: **Under Turf, Gardens, Shrubs, Trees**

## FEATURES

- High distribution uniformity surpassed only by the Eco-Mat
- Promotes healthier plant roots
- Eliminates overspray onto sidewalks, buildings, or vehicles
- Ideal for difficult areas between flagstone and pavers
- Use with PLD-Loc or barbed PLD fittings
- Fleece-wrapped professional landscape dripline
- Transports water faster and more uniformly than bare dripline
- Pressure compensating
- Check valves keep the line charged up to 5' and prevent low point drainage
- Fleece fully moistens in less than 3 minutes and conserves water that bare dripline cannot
- Recommended for use with all Hunter Drip Control Zone Kits
- Warranty period: 5 years (plus 2 additional years for environmental stress cracking)

## OPERATING SPECIFICATIONS

- Minimum filtration 120 mesh; 125 microns
- Operating pressure range: 15 to 50 PSI
- Compatible with PLD-LOC and 17 mm insert barb fittings

For maximum run length distances for the Eco-Mat or Eco-Wrap, reference the Maximum Run Length Chart on page 124. Use 0.6 GPH for flow and 12" emitter spacing.

ECO-WRAP TECHNICAL SPECIFICATIONS	
ECO-WRAP	17 mm
Flow and Spacing	0.6 GPH and 12"
Roll Length	250'
Operating Pressure	15 to 50 PSI
Minimum Filtration	120 mesh; 125 microns



Eco-Wrap

## APPLICATION RATE

EMITTER FLOW RATE - 0.4 GPH				EMITTER FLOW RATE - 0.6 GPH				EMITTER FLOW RATE - 1.0 GPH				QUICK REFERENCE CHART - GPM PER 100'			
Row Spacing (in.)	Emitter Spacing (in.)			Row Spacing (in.)	Emitter Spacing (in.)			Row Spacing (in.)	Emitter Spacing (in.)			Emitter (GPH)	Emitter Spacing (in.)		
	12	18	24		12	18	24		12	18	24		12	18	24
12	0.64	0.43	0.32	12	0.96	0.64	0.48	12	1.60	1.07	0.80	0.4	0.67	0.44	0.33
14	0.55	0.37	0.28	14	0.83	0.55	0.41	14	1.38	0.92	0.69	0.6	1.00	0.67	0.50
16	0.48	0.32	0.24	16	0.72	0.48	0.36	16	1.20	0.80	0.60	1.0	1.67	1.11	0.83
18	0.43	0.29	0.21	18	0.64	0.43	0.32	18	1.07	0.71	0.53	<b>Notes</b>			
20	0.39	0.26	0.19	20	0.58	0.39	0.29	20	0.96	0.64	0.48	Remember that for Eco-Mat, there are two laterals. Calculating GPM per 100' should reflect two lines, not just one.			
24	0.32	0.21	0.16	24	0.48	0.32	0.24	24	0.80	0.53	0.40				

**Notes**

Application rates in inches per hour

MICRO