

HPC

Combine the modularity of the Pro-C™ with Hydrawise® irrigation management software for a smart and flexible control solution.

KEY BENEFITS

- Number of stations:
 - Modular capacity from 4–16 stations permits simple system expansion
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 24-hour maximum station run time provides flexibility for low-flow zones
- 1 sensor input available for use with any Clik sensor or HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrawise software
- 7 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts

OPERATING SPECIFICATIONS

- Transformer input: 120 or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: Plastic IP44, UL, cUL, FCC, CE, RCM
- Warranty period: 2 years

USER-INSTALLED OPTIONS

- Wireless HC Flow Meter option permits wireless flow monitoring for Hydrawise enabled systems



HPC
(plastic indoor/outdoor)
Height: 22.9 cm
Width: 25.4 cm
Depth: 11.4 cm




HPC Face Panel

HPC	
Model	Description
HPC-400	4-station base: 120 VAC indoor/outdoor controller
HPC-401-E	4-station base: European 230 VAC indoor/outdoor controller
HPC-401-A	4-station base: Australian 230 VAC indoor/outdoor controller
HPC-FP	Hydrawise retrofit front panel for Pro-C controllers (March 2014 or newer models)

PC-SERIES STATION EXPANSION	
Model	Description
PCM-300	3-station plug-in module: Use to increase station count from 4 to 7, 10, or 13
PCM-900	9-station plug-in module: Use to increase station count from 7 to 16

Compatible with:



HC Flow Meter



**ROAM Remote
ROAM XL Remote**



**Rain-Clik
Sensor**



Smart WaterMark
Recognised as a responsible water-saving tool