IH RISERS

Flow: **2, 4, 8, 15, 23 I/hr**Surface Irrigation: **Robust Point Source Irrigation**

FEATURES

- · Heavy-duty, military-grade, vandal-resistant design
- · Made of flexible PVC for durability
- Brown components blend in with landscape
- Accepts any ½" FPT emitter
- · Ideal for slopes
- Pre-assembly reduces labour by up to 50%
- On grade or below grade installation
- · Available in multiple lengths for easy assembly
- Pre-assembled with ½" MPT adapter and specified emitter with check valve
- Available as components for custom assemblies
- · Check valve holds back 3.6 m of head
- Warranty period: 2 years

OPERATING SPECIFICATIONS

- Maximum flow: 26.5 I/min
- Maximum pressure: 4.1 bar; 410 kPa


IH RISER FLEXIBLE PVC		
Model	Description	
IH-RISER-06	15 cm flexible PVC riser	
IH-RISER-12	30 cm flexible PVC riser	
IH-RISER-18	45 cm flexible PVC riser	
IH-RISER-24	61 cm flexible PVC riser	
IH-RISER-36	91 cm flexible PVC riser	
IH-RISER-12-R	30 cm flexible PVC riser (reclaimed)	
IH-RISER-24-R	61 cm flexible PVC riser (reclaimed)	
IH-RISER-36-R	91 cm flexible PVC riser (reclaimed)	
SCREEN-CV	Filter screen with 2.7 m check valve	
IH-FIT-3850	¾" x ½" MPT IH fitting	
IH-FIT-3850-R	¾" x ½" MPT IH fitting (reclaimed)	
IH-250	76 m length of irrigation hose	
IPS-050-250	76 m length of 1/2" IPS	

IH Risers with Emitters - SPECIFICATION BUILDER: ORDER 1 + 2 + 3			
1 Riser Length	2 Flow with Check Valve Screen	3 Fitting Options	
IH-06 = 15 cm riser	05-CV = 2 l/hr	(blank) = Brown	
IH-12 = 30 cm riser	10-CV = 4 l/hr	R = Reclaimed	
IH-18 = 45 cm riser	20-CV = 8 l/hr	(purple fitting)	
IH-24 = 61 cm riser	40-CV = 15 l/hr		
IH-36 = 91 cm riser	60-CV = 23 l/hr		

Example:

IH-12-10-CV = 30 cm irrigation hose riser with 4 l/hr emitter with brown fittings





IH-FIT-3850 %" x ½" MPT IH fitting



IH-FIT-3850-R %" x ½" MPT IH fitting (reclaimed)





IPS-050-250

IH-250

Flexible PVC for creating headers or custom risers