

HPC

This smart and flexible control solution combines the modularity of the popular Pro-C™ Controller with the power of Hydrowise™ Software.

Try Hydrowise Software today at hydrowise.com.

KEY BENEFITS

- Number of stations:
 - Conventional wiring from 4 to 23 stations
 - Hybrid EZ Decoder System option up to 32 total stations (28 stations maximum if two-wire only)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 2 sensor inputs available for use with any Klik Sensor and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrowise Software
- 7 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts

OPERATING SPECIFICATIONS

- Transformer input: 120 or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- 2.4 GHz (only) Wi-Fi router compatible, 802.11 b/g/n 20 MHz
- Supported security protocols: WPA/WPA2 Personal (only), TLS
- Approvals: IP44 (outdoor), UL, cUL, FCC, CE, UKCA, RCM, ISED
- Warranty period: 2 years

USER-INSTALLED OPTIONS

- Wireless HC Flow Meter option permits wireless flow monitoring for Hydrowise enabled systems

HPC	
Model	Description
HPC-400	4-station base model, plastic wall mount cabinet, 120 VAC with U.S. cable and plug
HPC-401-E	4-station base model, plastic wall mount cabinet, 230 VAC with European cable and plug
HPC-401-A	4-station base model, plastic wall mount cabinet, 230 VAC with Australian cable and plug
HPC-FP	Hydrowise retrofit face panel for Pro-C Controllers (March 2014 or newer models)

PC-SERIES STATION EXPANSION	
Model	Description
PCM-300	3-station plug-in module
PCM-900	9-station plug-in module
PCM-1600	16-station plug-in module
PC-DM	EZ Decoder output module




HPC
(plastic indoor/outdoor)
Height: 22.9 cm
Width: 25.4 cm
Depth: 11.4 cm



HPC Face Panel


Compatible with:



HC Flow Meter
Page 158



ROAM Remote
Page 146
ROAM XL Remote
Page 147



EZ Decoder System
Page 142



Smart WaterMark
Recognised as a responsible water-saving tool