

# PRS30

PRESSURE REGULATED

Models: **Shrub, 10 cm, 15 cm, 30 cm**  
 Pressure Regulation: **2.1 bar; 210 kPa**

## FEATURES

- Models: Shrub, 10 cm, 15 cm, 30 cm
- No side inlet (NSI) version available in 15 cm and 30 cm
- Innovative directional flush plug design
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray® check valve
- ▶ Pressure regulated to 2.1 bar

## OPERATING SPECIFICATIONS

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa

## FACTORY INSTALLED OPTIONS

- Drain check valve (up to 4.3 m of elevation)
- Check valve available on 10 cm, 15 cm, 30 cm
- Reclaimed water ID cap

## USER INSTALLED OPTIONS

- Vandal-proof cap (P/N PROS-PRS30-VP)
- Drain check valve (up to 4.3 m of elevation; P/N 457400)
- Reclaimed water ID cap (P/N 458560)
- Snap-on reclaimed cover (P/N PROSRCCAP)
- ▶ = *Advanced Feature descriptions on page 56*



### PRS30 Reclaimed

PRS30 models include optional factory-installed purple reclaimed caps.



### Related Solutions: Works Best With

Pro-Spray Fixed Arc Nozzles and ProAdjustable Nozzles work best with the PRS30.

PRS30 - SPECIFICATION BUILDER: ORDER 1 + 2	
1 Model	2 Options
<b>PROS-00-PRS30</b> = 2.1 bar regulated shrub adapter	<b>(blank)</b> = No option  <b>CV</b> = Factory-installed drain check valve (pop-up models only) 15 cm and 30 cm models ordered as CV will come as no side inlet  <b>R</b> = Factory-installed reclaimed body cap (shrub molded in purple)
<b>PROS-04-PRS30</b> = 2.1 bar regulated 10 cm Pop-up	
<b>PROS-06-PRS30</b> = 2.1 bar regulated 15 cm Pop-up	
<b>PROS-06-NSI-PRS30</b> = 2.1 bar regulated 15 cm Pop-up (no side inlet)	
<b>PROS-12-PRS30</b> = 2.1 bar regulated 30 cm Pop-up	
<b>PROS-12-NSI-PRS30</b> = 2.1 bar regulated 30 cm Pop-up (no side inlet)	

### Examples:

**PROS-04-PRS30** = 10 cm Pop-up regulated at 2.1 bar; 210 kPa

**PROS-06-PRS30 - CV** = 15 cm Pop-up regulated at 2.1 bar; 210 kPa, drain check valve

**PROS-12-PRS30 - CV - R** = 30 cm Pop-up regulated at 2.1 bar; 210 kPa, drain check valve, and reclaimed body cap



### PROS-00-PRS30

Retracted height: 11 cm  
 Inlet size: ½"



### PROS-04-PRS30

Retracted height: 15.5 cm  
 Pop-up height: 10 cm  
 Exposed diameter: 5.7 cm  
 Inlet size: ½"



### [A] PROS-06-PRS30

Retracted height: 22.5 cm  
 Pop-up height: 15 cm  
 Exposed diameter: 5.7 cm  
 Inlet size: ½"



### [B] PROS-06-NSI-PRS30

Retracted height: 22.5 cm  
 Pop-up height: 15 cm  
 Exposed diameter: 5.7 cm  
 Inlet size: ½"



### [A] PROS-12-PRS30

Retracted height: 41 cm  
 Pop-up height: 30 cm  
 Exposed diameter: 5.7 cm  
 Inlet size: ½"



### [B] PROS-12-NSI-PRS30

Retracted height: 41 cm  
 Pop-up height: 30 cm  
 Exposed diameter: 5.7 cm  
 Inlet size: ½"